



core
WEB
programming

HyperText Markup Language (HTML)

Designing Documents for the
World Wide Web

© 2001-2003 Marty Hall, Larry Brown <http://www.corewebprogramming.com>

Agenda

- Introduction to HTML
- Creating and publishing a Web page
- Validating a document
- Main HTML elements
- Block-level HTML elements
- Text-level HTML element
- Creating hypertext links
- Adding images to documents
- Building tables

The World Wide Web

- **Definitions**

- The World Wide Web
 - The set of computers on the Internet that support HTTP
 - Not a separate network
- HTTP
 - The HyperText Transfer Protocol
 - The language used by a WWW client (e.g. Netscape, Internet Explorer) to request documents from a WWW server (i.e. the program running at Web sites like amazon.com or yahoo.com)
- HTML
 - The HyperText Markup Language
 - The language used to design web pages

HyperText Markup Language

- **Text Mixed with Markup Tags**

- Tags Enclosed in Angle Brackets
(`<H1>Introduction</H1>`)

- **What Does Markup Describe?**


- Appearance
- Layout
- Content (Can't Enforce an Exact Look)

- **Changes in HTML 3.2 to HTML 4.0**

- Standardization of frames
- Deprecation of formatting elements (vs. style sheets)
- Improved cell alignment and grouping in tables
- Mouse and keyboard events for nearly all elements
- Internationalization features

HTML Example

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML>
<HEAD>
  <Title>Home Page for Lawrence M. Brown</Title>
</HEAD>
<BODY BGCOLOR="WHITE">
<H1 ALIGN="CENTER">Home Page for Lawrence M. Brown</H1>
<HR>
<IMG SRC="images/nswc.jpg"
      HSPACE=10 VSPACE=10 alt="NSWC Logo" />
Senior Network Engineer
<A HREF="http://www.corewebprogramming.com">www.corewebprogramming.com</A>
Naval Surface Warfare Center
9500 MacArthur Boulevard
West Bethesda, Maryland, MD 20817-5700
<I>email: </I> <A HREF="mailto:brown@corewebprogramming.com">brown@corewebprogramming.com</A>
<I>Phone: </I> (301) 277-4648
<P>
This is my personal home page. For more specific programming-related resources pages, please see:
<!-- Rest of Sample HTML -->
</BODY>
</HTML>
```



5

Creating and Publishing a Web Page

1. Create an HTML document
2. Place the document in a world-accessible directory (often `public_html` or `www`) on a system running an HTTP server

```
Unix> cd
Unix> chmod a+x . (Note the ".")
Unix> mkdir public_html
Unix> chmod a+x public_html
```

3. Access the web page through `http://hostname/~username/filename`
 - E.g. `http://www.ap1.jhu.edu/~lmb/test.html`
 - If the filename is omitted, a system default filename is assumed (often `index.html`)
 - E.g. `http://www.ap1.jhu.edu/~hall/` refers to the file `index.html` in hall's `public_html` directory

6

HTML

www.corewebprogramming.com

Creating and Publishing a Web Page, cont.

4. Validate the Document

- Check the syntax using a formal HTML validator
 - <http://validator.w3.org/>
 - <http://www.htmlhelp.com/tools/validator/>
- The version of HTML against which the document is validated is based on the DOCTYPE
`<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">`
- The WWW Consortium recently added advice that Web pages include information on the character set, even though ASCII or Latin-1 is the default. The validator at <http://validator.w3.org/> gives warnings if you omit this. You can ignore such warnings if you wish.

7

HTML

www.corewebprogramming.com

HTML Document Template

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML>
<HEAD>
  <TITLE>Title</TITLE>
</HEAD>

<BODY>
<H1>Main Heading</H1>


<!-- Rest of page goes here -->

</BODY>
</HTML>
```

← Goes on browser's title bar
May not appear in printouts

← Main heading. Often used as title
Appears in printouts

← HTML comment
Replace with body of
WWW page



8

HTML

www.corewebprogramming.com

Main HTML Elements

1. DOCTYPE

2. HTML

3. HEAD

- TITLE element required
- Optional elements:
 - BASE
 - META
 - BGSOUND
 - SCRIPT, NOSCRIPT
 - STYLE
 - LINK

Main HTML Elements (Continued)

4. BODY Element

- `<BODY BGCOLOR="YELLOW">`
- HTML Attributes and Attribute Values
 - BACKGROUND
 - BGCOLOR
 - TEXT
 - LINK, VLINK, ALINK
 - OnLoad, OnUnload, OnFocus, OnBlur

5. Elements inside BODY element

- `<BODY>`
Remaining HTML elements
`</BODY>`

META Element

- **Records document information, forwards and refreshes pages**
 - NAME="author"
 - NAME="keywords"
 - NAME="description"
 - HTTP-EQUIV="refresh"

META Element, Example

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML>
<HEAD>
  <TITLE>News Headlines</TITLE>
  <META HTTP-EQUIV="REFRESH"
    CONTENT="3600">
</HEAD>

<BODY>
<H1 ALIGN="CENTER">News Headlines</H1>

<H2>National News</H2>
Blah, blah, blah.

<H2>International News</H2>
Yadda, yadda, yadda.

</BODY>
</HTML>
```

Block-Level Elements

- **Headings**
 - H1 ... H6
 - ALIGN
- **Basic Text Sections**
 - P
 - ALIGN
 - PRE
 - WIDTH
 - ADDRESS
 - BLOCKQUOTE

Block-Level Elements, cont.

- **Lists**
 - OL
 - LI
 - UL
 - LI
 - DL
 - DT
 - DD
- **Tables and Forms (Postponed)**
- **Misc.**
 - HR
 - DIV
 - CENTER
 - MULTICOL (Netscape only)

Headings

- **Heading Types**

- `<H1 ...> ... </H1>`
- `<H2 ...> ... </H2>`
- `<H3 ...> ... </H3>`
- `<H4 ...> ... </H4>`
- `<H5 ...> ... </H5>`
- `<H6 ...> ... </H6>`

- **Attributes: ALIGN**

- Values: LEFT (default), RIGHT, CENTER


- **Nesting tags**

- Headings and other block-level elements can contain text-level elements, but *not* vice versa

Headings, Example

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML>
<HEAD>
  <TITLE>Document Headings</TITLE>
</HEAD>
<BODY>
  Samples of the six heading types:
  <H1>Level-1 (H1)</H1>
  <H2 ALIGN="CENTER">Level-2 (H2)</H2>
  <H3><U>Level-3 (H3)</U></H3>
  <H4 ALIGN="RIGHT">Level-4 (H4)</H4>
  <H5>Level-5 (H5)</H5>
  <H6>Level-6 (H6)</H6>
</BODY>
</HTML>
```


Headings, Result



17

HTML

www.corewebprogramming.com

P – The Basic Paragraph

- **Attributes: ALIGN**

- LEFT (default), RIGHT, CENTER. Same as headings.
- Whitespace ignored (use
 for line break)
 - Consecutive <P>'s do not yield multiple blank lines
- End Tag is Optional:

```
<BODY>
<P>
Paragraph 1
</P>
<P>
Paragraph 2
</P>
<P>
Paragraph 3
</P>
</BODY>
```

Fully-Specified

```
<BODY>
Paragraph 1
<P>
Paragraph 2
<P>
Paragraph 3
</BODY>
```

Equivalent with Implied Tags

18

HTML

www.corewebprogramming.com

Preformatted Paragraphs

- **The PRE Element**

- `<PRE> ... </PRE>`

- **Attributes: WIDTH**

- Expected width in characters. Not widely supported.

- **Problem: Special Characters**

```
<PRE>
```

```
if (a<b) {  
    doThis();  
} else {  
    doThat();  
}  
</PRE>
```

Desired Character	HTML Required
<	<
>	>
&	&
"	"
Non-breaking space	

OL: Ordered (Numbered) Lists

- **OL Element**

- ``
 `...`
 `...`

 ``

- Attributes: TYPE, START, COMPACT

- **List entries: LI**

- `<LI ...> ... ` (End Tag Optional)

- Attributes: (When inside OL) VALUE, TYPE

A sample list:

```
<OL>  
  <LI>List Item One  
  <LI>List Item Two  
  <LI>List Item Three  
</OL>
```

A sample list:

```
1. List Item One  
2. List Item Two  
3. List Item Three
```

Nested Ordered Lists

```
<OL TYPE="I">
<LI>Headings
  <LI>Basic Text Sections
    <LI>Lists
      <OL TYPE="A">
        <LI>Ordered
          <OL TYPE="1">
            <LI>The OL tag
              <OL TYPE="a">
                <LI>TYPE
                <LI>START
                <LI>COMPACT
              </OL>
            <LI>The LI tag
          </OL>
        <LI>Unordered
          <OL TYPE="1">
            <LI>The UL tag
            <LI>The LI tag
          </OL>
        <LI>Definition
          <OL TYPE="1">
            <LI>The DL tag
            <LI>The DT tag
            <LI>The DD tag
          </OL>
      </OL>
    <LI>Miscellaneous
  </LI>
</LI>
</OL>
```

```
I. Headings
II. Basic Text Sections
III. Lists
  A. Ordered
    1. The OL tag
      a. TYPE
      b. START
      c. COMPACT
    2. The LI tag
  B. Unordered
    1. The UL tag
    2. The LI tag
  C. Definition
    1. The DL tag
    2. The DT tag
    3. The DD tag
IV. Miscellaneous
```

21

www.corewebprogramming.com

UL: Unordered (Bulleted) Lists

• UL Element

```
- <UL>
  <LI>...
  <LI>...
  ...
</UL>
```

• Attributes: TYPE, COMPACT

- TYPE is DISC, CIRCLE, or SQUARE

• List entries: LI (TYPE)

- TYPE is DISC, CIRCLE, or SQUARE

A sample list:

```
<UL>
  <LI>List Item One
  <LI>List Item Two
  <LI>List Item Three
</UL>
```

A sample list:

- List Item One
- List Item Two
- List Item Three

22

HTML

www.corewebprogramming.com

UL: Custom Bullets

```
<UL TYPE="DISC">
  <LI>The UL tag
    <UL TYPE="CIRCLE">
      <LI>TYPE
        <UL TYPE="SQUARE">
          <LI>DISC
          <LI>CIRCLE
          <LI>SQUARE
        </UL>
      <LI>COMPACT
    </UL>
  <LI>The LI tag
    <UL TYPE="CIRCLE">
      <LI>TYPE
        <UL TYPE="SQUARE">
          <LI>DISC
          <LI>CIRCLE
          <LI>SQUARE
        </UL>
      <LI>VALUE
    </UL>
  </UL>
```

Unordered Lists

- The UL tag
 - TYPE
 - DISC
 - CIRCLE
 - SQUARE
 - COMPACT
- The LI tag
 - TYPE
 - DISC
 - CIRCLE
 - SQUARE
 - VALUE

23

HTML

www.corewebprogramming.com

Text-Level Elements

- **Physical Character Styles**
 - B, I, TT, U, SUB, SUP, SMALL, BIG, STRIKE, S, BLINK
 - FONT
 - SIZE
 - COLOR
 - FACE
 - BASEFONT
 - SIZE
- **Logical Character Styles**
 - EM, STRONG, CODE, SAMP, KBD, DFN, VAR, CITE

24

HTML

www.corewebprogramming.com

Text-Level Elements (Continued)

- **Hypertext Links**

- A
 - HREF, NAME, TARGET, ...

- **Images**

- IMG
 - SRC (required), ALT, ALIGN, WIDTH, HEIGHT, HSPACE, VSPACE, BORDER, USEMAP, ISMAP


- **Misc. Text-Level Elements**

- BR (Explicit line break)
- AREA (Client-side image maps)
- APPLET (Java)
- ...

Physical Character Styles, Example

```
...
<H1>Physical Character Styles</H1>
<B>Bold</B><BR>
<I>Italic</I><BR>
<TT>Teletype (Monospaced)</TT><BR>
<U>Underlined</U><BR>
Subscripts: f<SUB>0</SUB> + f<SUB>1</SUB><BR>
Superscripts: x<SUP>2</SUP> + y<SUP>2</SUP><BR>
<SMALL>Smaller</SMALL><BR>
<BIG>Bigger</BIG><BR>
<STRIKE>Strike Through</STRIKE><BR>
<B><I>Bold Italic</I></B><BR>
<BIG><TT>Big Monospaced</TT></BIG><BR>
<SMALL><I>Small Italic</I></SMALL><BR>
<FONT COLOR="GRAY">Gray</FONT><BR>
<DEL>Delete</DEL><BR>
<INS>Insert</INS><BR>
...
```

Physical Character Styles, Result



27

HTML

www.corewebprogramming.com

Logical Character Styles, Example


```
...
<H1>Logical Character Styles</H1>
<EM>Emphasized</EM><BR>
<STRONG>Strongly Emphasized</STRONG><BR>
<CODE>Code</CODE><BR>
<SAMP>Sample Output</SAMP><BR>
<KBD>Keyboard Text</KBD><BR>
<DFN>Definition</DFN><BR>
<VAR>Variable</VAR><BR>
<CITE>Citation</CITE><BR>
<EM><CODE>Emphasized Code</CODE></EM><BR>
<FONT COLOR="GRAY"><CITE>Gray Citation</CITE></FONT><BR>
<ACRONYM TITLE="Java Development Kit">JDK Acronym</ACRONYM>
...
```

28

HTML

www.corewebprogramming.com

Logical Character Styles, Result



29

HTML

www.corewebprogramming.com

Hypertext Links

- **Links can contain images and other text-level elements (i.e., `<A HREF...> ... `)**
- **Link to Absolute URL**
 - Use a complete URL beginning with `http://`
Java is discussed in
``
Chapter 2.
- **Link to Relative URL**
 - Use a filename or relative path to filename
 - Interpreted wrt location of current file
Java is discussed in
`Chapter 2`.

30

HTML

www.corewebprogramming.com

Hypertext Links (Continued)

- **Link to Section**

- Use a section name (see below) preceded by #
Images are discussed in
`Section 2.`

- **Link to Section in URL**

- Use absolute or relative URL, then #, then section name
Images are discussed in
`
Sec. 2 of Chap. 1.`

- **Naming a Section**

- Use `` and do not include the pound sign
`<H2>Images</H2>`

31

HTML

www.corewebprogramming.com

IMG: Embedding Images

- **Example**

```
<IMG SRC="SomeFile.gif" ALT="My Dog"  
WIDTH=400 HEIGHT=300>
```

- **Attributes:**

- SRC (required)
- ALT (technically required)
- ALIGN (see `<BR CLEAR="ALL">`)
- WIDTH, HEIGHT
- HSPACE, VSPACE
- BORDER
- USEMAP, ISMAP

32

HTML

www.corewebprogramming.com


Image Alignment, Example

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML>
<HEAD><TITLE>Image Alignment</TITLE></HEAD>
<BODY>
<H1 ALIGN="CENTER">Image Alignment</H1>
<TABLE BORDER=1>
  <TR><TH>Alignment
    <TH>Result
  <TR><TH><CODE>LEFT</CODE>
    <TD><IMG SRC="rude-pc.gif" ALIGN="LEFT"
      ALT="Rude PC" WIDTH=54 HEIGHT=77>
      This positions the image at the left side,
      with text flowing around it on the right.
  <TR><TH><CODE>RIGHT</CODE>
    <TD><IMG SRC="rude-pc.gif" ALIGN="RIGHT"
      ALT="Rude PC" WIDTH=54 HEIGHT=77>
      This positions the image at the right side,
      with text flowing around it on the left.
    . . .
  </TABLE>
</BODY>
</HTML>
```

33

www.corewebprogramming.com

Image Alignment, Result



34

HTML

www.corewebprogramming.com

Tables

- **Template**

```
<TABLE BORDER=1>  
  <CAPTION>Table Caption</CAPTION>  
  <TR><TH>Heading1</TH>      <TH>Heading2</TH></TR>  
  <TR><TD>Row1 Col1 Data</TD><TD>Row1 Col2 Data</TD></TR>  
  <TR><TD>Row2 Col1 Data</TD><TD>Row2 Col2 Data</TD></TR>  
  <TR><TD>Row3 Col1 Data</TD><TD>Row3 Col2 Data</TD></TR>  
</TABLE>
```

Heading1	Heading2
Row1 Col1 Data	Row1 Col2 Data
Row2 Col1 Data	Row2 Col2 Data
Row3 Col1 Data	Row3 Col2 Data

TABLE Element Attributes

- **ALIGN**

- The ALIGN attribute gives the horizontal alignment of the table as a whole
- Legal values are LEFT, RIGHT, and CENTER, with LEFT being the default

- **BORDER**

- This specifies the width in pixels of the border around the table
- This is in addition to the border around each cell (the CELLSPACING).
- The default is zero, which also results in the visible 3D divider between cells being turned off

- **CELLSPACING**

- This gives the space in pixels between adjacent cells. Drawn as a 3D line if BORDER is nonzero, otherwise empty space in the background color is used
- The default is usually about 3

TABLE Element Attributes (Continued)

- **CELLPADDING**

- CELLPADDING determines the empty space, in pixels, between the cell's border and the table element
- The default is usually about 1

- **WIDTH**

- This specifies the width of the table, either in pixels (<TABLE WIDTH=250>) or as a percentage of the current browser window width (<TABLE WIDTH="75%">)

- **BGCOLOR**

- Specify the background color of the table TABLE (also legal for TR, TD, and TH)

- **BORDERCOLOR, BORDERCOLORDARK,**

- **BORDERCOLORLIGHT**

- Non standard attributes supported by IE to specify the colors to use for the borders

TABLE Element Attributes (Continued)

- **BACKGROUND**

- This nonstandard attribute supported by IE gives an image file that will be tiled as the background of the table
- You might want to use style sheets instead.

- **RULES**

- HTML 4.0 attribute that specifies which inner dividing lines are drawn
- All are drawn if this attribute is omitted
- Legal values are NONE, ROWS, COLS, and ALL

- **FRAME**

- Specifies which outer borders are drawn
- All four are drawn if this attribute is omitted
- Legal values are BORDER or BOX (all), VOID (none), ABOVE (top), BELOW (bottom), HSIDES (top and bottom, despite the somewhat confusing name), VSIDES (left and right), LHS (left), and RHS (right)

Table CAPTION

- **Attribute**
 - ALIGN (Values: TOP, BOTTOM)
- **Usage**
 - An enclosing borderless table may give more flexibility than the built-in CAPTION.

Heading1	Heading2
Row1 Col1 Data	Row1 Col2 Data
Row2 Col1 Data	Row2 Col2 Data
Row3 Col1 Data	Row3 Col2 Data

TR: Table Row

- **TR is used to define each row in the table**
- **Each row will then contain TH and/or TD entries**
- **ALIGN**
 - ALIGN (legal values LEFT, RIGHT, or CENTER) is used to set the default horizontal alignment for table cells
- **VALIGN**
 - VALIGN (legal values TOP, MIDDLE, or BOTTOM) is used to set the default vertical alignment for table cells
- **BGCOLOR**
 - Sets the color for the table row, overriding any values set for the table as a whole via the BGCOLOR attribute of TABLE
- **BORDERCOLOR, BORDERCOLORDARK,**
- **BORDERCOLORLIGHT**
 - Supported only by Internet Explorer, these specify the colors to use for the row borders

Table Cells: TH and TD

- **COLSPAN**

- COLSPAN defines a heading or cell data entry that spans multiple columns

```
<TABLE BORDER=1>
<TR><TH COLSPAN=2>Col 1&2 Heading
      <TH>Col3 Heading
<TR><TD>Col1 Data
      <TD>Col2 Data
      <TD>Col3 Data
</TABLE>
```

Col 1&2 Heading		Col3 Heading
Col1 Data	Col2 Data	Col3 Data

41

HTML

www.corewebprogramming.com

Table Cells: TH and TD (Continued)

- **ROWSPAN**

- ROWSPAN defines a heading or cell data entry that spans multiple rows; similar to COLSPAN

- **ALIGN**

- LEFT, RIGHT, CENTER, JUSTIFY and CHAR.
- E.g., the following aligns entries on a decimal point

```
<TD ALIGN="CHAR" CHAR=".">
```

- **VALIGN**

- TOP, BOTTOM, MIDDLE

- **WIDTH, HEIGHT**

- Values in pixels only (no percentages officially allowed)

- **NOWRAP**

- Use with caution

- **BGCOLOR, BACKGROUND**

- Same as for TABLE and TR

42

HTML

www.corewebprogramming.com

Summary

- **A DOCTYPE is required to validate the document**
- **HTML document should have an enclosing HTML element, a HEAD (TITLE is required) and a BODY**
- **Documents are composed of block-level and text-level elements**
 - Text-level elements must be inside block-level elements, not vice versa
- **Hypertext links, ``, can be absolute or relative**
 - A link to a named section is denoted by *#section*
- **Tables are composed of main table element, `<TABLE>`; rows, `<TR>`; table headers, `<TH>`; and table data, `<TD>`**
 - Use BGCOLOR to give background colors to tables, rows, or cells
 - Use ROWSPAN or COLSPAN to join cells

43

HTML

www.corewebprogramming.com



core
WEB
programming

Questions?

44

© 2001-2003 Marty Hall, Larry Brown <http://www.corewebprogramming.com>